

# MCap SUPREME

Very soon after its market launch in 1992 the

MCap<sup>®</sup> SUPREME Classic has been internationally acclaimed as top-class capacitor. Today it is considered by many users as a milestone in the modern audiophile capacitor generation.

The self-healing PP capacitor film used here is first metallized with the thickest possible aluminium layer, then wound precisely into distinctive SUPREME winding geometry and finally potted by hand into special aluminium cans to minimize microphony.

These features are reflected in the music reproduction with their holographic three-dimensionality and outstanding tonal balance.



#### Specifications:

Dielectric: Polypropylene

Dielectric strength: 600-1400 VDC

Loss angle:  $\tan\delta = 0.0002@1\text{ kHz}; 0.0001@10\text{ kHz}$

Permissible ambient temperature 85°C/185°F



## MCap SUPREME Classic

Order Code	Capacity [ $\mu\text{F}$ ]	[VDC]	Body $\text{\O} * \text{L}$ [mm]	Wire $\text{\O} * \text{L}$ [mm]
SUP8-0.10	0.10 $\pm 2\%$	1400	17 * 36	0.8 * 60
SUP8-0.22	0.22 $\pm 2\%$	1400	20 * 38	1.0 * 60
SUP8-0.33	0.33 $\pm 2\%$	1400	25 * 56	1.0 * 60
SUP8-0.47	0.47 $\pm 2\%$	1000	20 * 39	1.0 * 60
SUP8-0.68	0.68 $\pm 2\%$	600	20 * 39	1.0 * 60
SUP8-1.00	1.0 $\pm 2\%$	600	20 * 39	1.0 * 60
SUP8-1.50	1.5 $\pm 2\%$	600	25 * 52	1.0 * 60
SUP8-1.80	1.8 $\pm 2\%$	600	25 * 52	1.0 * 60
SUP8-2.20	2.2 $\pm 2\%$	600	25 * 52	1.0 * 60
SUP8-2.70	2.7 $\pm 2\%$	600	30 * 56	1.0 * 60
SUP8-3.30	3.3 $\pm 2\%$	600	30 * 56	1.4 * 60
SUP8-3.90	3.9 $\pm 2\%$	600	30 * 56	1.4 * 60
SUP8-4.70	4.7 $\pm 2\%$	600	36 * 56	1.4 * 60
SUP8-5.60	5.6 $\pm 2\%$	600	36 * 56	1.4 * 60
SUP8-6.80	6.8 $\pm 2\%$	600	41 * 53	1.4 * 60
SUP8-8.20	8.2 $\pm 2\%$	600	36 * 106	1.4 * 60
SUP8-10	10 $\pm 2\%$	600	36 * 106	1.4 * 60
SUP8-15	15 $\pm 2\%$	600	41 * 106	1.4 * 60
SUP8-18	18 $\pm 2\%$	600	41 * 106	1.4 * 60
SUP8-22	22 $\pm 2\%$	600	50 * 106	1.4 * 60