

Fidelity Components M-Cap

M-Cap[®] SUPREME
silver/gold

The metallization of the capacitor foil for our **M-Cap[®] SUPREME silver/gold** consists of pure silver with an admixture of 1% pure gold. Gold alters the crystalline structure of silver and maximises its very good electrical conductivity. The outstanding properties of the M-Cap[®] SUPREME - high definition and auditory ambiance of the music playback - are once again audibly enhanced and substantially enriched in finely nuanced timbres through the utilisation of silver/gold. (see also p. 9, about the advantage of induction-free SUPREME winding technology)


We are convinced that with this capacitor we have once again lived up to our reputation for innovation and quality as one of the internationally leading manufacturers of audiophile components.

In this capacitor **M-Cap[®] SUPREME silver/gold** speed and precision combine harmonically with beauty and elegance.



Technical specifications:

Capacitance: 0.01µF-10µF
Dielectric: Polypropylene
Metallisation: 99.99% silver, 1% gold
Purity of silver: min. 99.97% typ. 99.99%
Purity of gold: min. 99.97% typ. 99.99%
Dielectric strength: 1 200V DC
Loss factor $\tan \delta$: 0.0002@1 kHz, 0.0001@10 kHz



sup_s_g

Supreme capacitors silver/gold

Capacity [µF] ±2%	VDC	Body Ø * L [mm]	Wire Ø [mm]
0.0010	1200	17 * 36	0.6
0.0033	1200	17 * 36	0.6
0.0047	1200	17 * 36	0.6
0.010	1200	17 * 36	0.6
0.015	1200	17 * 36	0.6
0.022	1200	17 * 36	0.6
0.033	1200	17 * 36	0.6
0.047	1200	17 * 36	0.6
0.056	1200	17 * 36	1.0
0.068	1200	17 * 36	1.0
0.082	1200	17 * 36	1.0
0.10	1200	17 * 36	1.0
0.15	1200	17 * 36	1.0
0.22	1200	19 * 39	1.0
0.33	1200	19 * 39	1.0
0.47	1200	26 * 41	1.4
0.56	1200	26 * 41	1.4
0.68	1200	26 * 41	1.4
0.82	1200	31 * 42	1.4
1.00	1200	31 * 42	1.4
1.5	1200	36 * 42	1.4
1.8	1200	41 * 54	1.4
2.2	1200	36 * 56	1.4
2.7	1200	36 * 56	1.4
3.3	1200	41 * 57	1.4
3.9	1200	41 * 57	1.4
4.7	1200	46 * 71	1.4
5.6	1200	46 * 71	1.4
6.8	1200	51 * 71	1.4
8.2	1200	51 * 71	1.4
10	1200	51 * 106	1.4