

215-2000

Full range drive unit



The 215-2000 is a full range speaker and high efficiency driver unit. No compromise for this loudspeaker of exception: hyperbolic cone paper without bicone, suspension with the max. displacement of 2cm, Alnico driving block (3.5Kg) and pure iron core to obtain 21000 Gauss of magnetic field. The 215-2000 astonishes by its precision and its clearness in the medium, by the presence without aggressiveness of high frequencies, by the speed and the clearness of its low register, the whole with exceptional dynamics. In column TQWT or in enclosure of back horn type, it justifies its row of ultimate full range loudspeaker.

Mesurement curves

[Page 1](#)

[Page 2](#)

215-2000 Specifications

Efficiency 1 W/1m at Fs	99 dB	Fs	47Hz
Frequency response	50 à 20kHz	Re	4 ohms
Impedance	4 ohms	Qts	0.23
Power max. RMS	20 W	Qe	0.24
Weight	7.1 kg	Qm	8
Suspension	5 plis papier	Vas	121 L
Linear excursion	10 mm	Bl	6.5
Magnet diameter	3.5 kg	Cms	1
Magnetic field	2.1 T	Mms	7g
Diameter HP	224/237mm	Sd	283 cm ²
Frame thickness	Alu 10mm		
Diameter fixation holes	227 mm		
Diameter drilling enclosure	212 mm		
Depth HP	147 mm		