

# 215 RTF 64 Bicone

Full range driver unit



Resulting from the 215 rtf, high speaker of legend, full range and high efficiency, the model bicone offers to you in the field of the installation of exception a listening of an exceptional coherence.

Thanks to its very wide frequency response it can be assembled in one way enclosures without filtering. Equipped with a powerful magnetic circuit, of a moving element very light and made up of an exponential membrane, it reaches a level of precision of the restitution worthy of best the installations.

InsideGone a TQWT enclosure, with resonators or of back horn type the answer extends from 50Hz up to 18000 Hz with  $\pm 3$  dB.

## Mesurement curves

[Page 1](#)

[Page 2](#)

## 215 RTF 64 BICONE Specifications

Efficiency 1 W/1m at Fs	96 dB	Fs	52 Hz
Frequency response	50 à 20kHz	Re	6.5
Impedance	8 ohms	Qts	0.53
Power max. RMS	35 W	Qe	0.6
Weight	2.8 kg	Qm	5
Suspension	3 plis papier	Vas	75 L
Linear excursion	4 mm	Bl	5.3
Magnet diameter	120 mm	Cms	0.8
Magnetic field	1.5 T	Mms	9.5 g
Diameter HP	224/237mm	Sd	263 cm <sup>2</sup>
Frame thickness	Alu 10mm		
Diameter fixation holes	227 mm		
Diameter drilling enclosure	212 mm		
Depth HP	100 mm		