

215 RTF 64

Full range driver unit



This full range driver unit and high efficiency is not other than evolution 95 of the HP of legend which equipped the studios of the house of the radio, the ORTF, of the RAI, RTL and EUROPE 1. Approved opera, it gets a cordial listening with the clear and precise medium and offers multiple possibilities of assembly. Ideal listening with an amplifier (tube or transistor) of low power of approximately 10W.

In open baffle, the spacial presence of the sound will enchant you, the HP expresses its great dynamics as well as possible. In TQWT it will emphasize all the smoothness of your preferred listenings. This HP can be reinforced by a tweeter of the type JBL 2405 or B&C D-32 with a simple cut with 10kHz by one wrapped of 0.47 or 0.33 uF. The low register can be reinforced, in particular in open baffle by the 285 or the 400 SUPRAVOX cut at 100Hz.

Mesurement curves

[Page 1](#)

[Page 2](#)

215 RTF 64 Specifications

Efficiency 1 W/1m at Fs	97 dB	Fs	60 Hz
Frequency response	50 à 10kHz	Re	6.5 ohms
Impedance	8 ohms	Qts	0.58
Power max. RMS	35 W	Qe	0.6
Weight	2.8 kg	Qm	7
Suspension	3 plis papier	Vas	80 L
Linear excursion	4 mm	Bl	5.8
Magnet diameter	120 mm	Cms	0.8
Magnetic field	1.5 T	Mms	8.5 g
Diameter HP	224/237mm	Sd	263 cm ²
Frame thickness	Alu 10mm		
Diameter fixation holes	227 mm		
Diameter drilling enclosure	212 mm		
Depth HP	100 mm		