

285 GMF

Bass medium drive unit.



This high efficiency drive unit offer a very fast low register to you and pleasant listening. Ideal listening with an amplifier of low power (tube or transistor) of approximately 10W, it supports also stronger powers for a use out of low register boxes. In open baffle, it will reinforce, with the same degree of accuracy of reproduction the 215 rtf, to add a low register reinforcement to him and to ensure a comfortable and balanced listening. In column TQWT it will emphasize all the smoothness of your preferred listenings. In RJ box, bass reflex or symmetrical, it will be a low register of accompaniment of most precise. This driver unit could be coupled with an 1 inch driver + horn. Crossed with 500Hz the response curve will be right with ± 2 dB from 35 to 20 000Hz.

Mesurement curves

[Page 1](#)

[Page 2](#)

Spécifications 285 GMF

Efficiency 1 W/1m at Fs	99 dB	Fs	47Hz
Frequency response	40 à 7kHz	Re	6.5 ohms
Impedance	8 ohms	Qts	0.38
Power max. RMS	70 W	Qe	0.39
Weight	3.5 kg	Qm	8
Suspension	3 plis papier	Vas	150 L
Linear excursion	8 mm	Bl	10.7
Magnet diameter	120 mm	Cms	0.6
Magnetic field	1.4 T	Mms	20 g
Diameter HP	290/307mm	Sd	471 cm ²
Frame thickness	Alu 8mm		
Diameter fixation holes	294 mm		
Diameter drilling enclosure	280 mm		
Depth HP	128 mm		