



**BULL AUDIO 2006**



### **CS-650.75**

2-way

6.5 Inch Compo-Set

Max. 100 Watt

Part-No. : 350905

### **CS-525.75**

2-way

5.25 Inch Compo-Set

Max. 80 Watt

Part-No. : 350904



- Powder coated basket
- PP cone for tight and crisp Kick bass
- 20 cm neodymium tweeter made of silk with Ferrofluid cooling
- Crossover with tweeter attenuation and reversible overload protection
- Flush mount and angle mount included

- Einbaukorb pulverbeschichtet
- PP Membrane für satten Kick-Bass
- 20 cm Neodym-Hochtöner aus Seide mit Ferrofluid Kühlung
- Weiche mit Hochtön-Absenkung und reversiblen Überlastschutz
- Einbautopf mit Winkeleinstellung und Schrägpult

COMPO SET

# COAX / TRIAX

## COA-650

6.5 Inch Coaxial-Set  
Max. 100 Watt  
Part-No. : 350907



- Powder coated basket
- PP cone for tight and crisp Kick bass
- 15 mm foil tweeter dome
- Integrated crossover and reversible tweeter overload protection
- Tweeter connection through magnet

- Einbaukorb pulverbeschichtet
- PP Membrane für satten Kick-Bass
- 15 mm Neodym-Hochtöner aus Folie
- Integrierte Weiche mit reversiblen Hochtöner-Überlastschutz
- Hochtönerkabelanschluss durch den Magnet

## COA-525

5.25 Inch Coaxial-Set  
Max. 80 Watt  
Part-No. : 350906



## TRI-6090

6x9 Inch Triaxial-Set  
Max. 140 Watt  
Part-No. : 350908



### **ESW-12**

12 Inch Enclosure Ported  
Max. 400 Watt  
Part-No. : 350903

- 22 mm Medium density fibreboard/ particle board compound glued
- Screwed, airtight enclosure for dynamic load capacity
- Chromium-plated terminal for 2 x 4 mm<sup>2</sup> cable
- Solid stainless steel protector rods to prevent speaker cone damage
- Kinky deep bass thanks to optimized aero-ports and enclosure calculation

- 22 mm MDF / Spanplatten als Compound verleimt
- Gehäuse verschraubt und luftdicht verleimt für extrem hohe Belastbarkeit
- Verchromtes Anschlussterminal 2 x 4 mm<sup>2</sup>
- Stabile V3A-Schutzstäbe verhindern Schäden an der Membrane
- Abartiger Tiefbass durch optimierte Gehäuseberechnung und Aero-Ports.

4 ENCLOSURE

# SUBWOOFER



- Folded steel basket
- Polypropylene cone for tight and crisp sub bass
- Chromium-plated push terminals for large cable diameters
- Large ferror-ceramics magnet for high SPL
- Extended pole piece for large excursion
- Suitable for enclosures from 20 litres
- Application: bandpass, ported, or sealed

- Höchwertiger Faltstahlkorb für maximale Steifigkeit
- PP Membrane für satten und kräftigen Sub-Bass
- Verchromte Push-Terminals für große Kabelquerschnitte
- Großer Eisen-Strontium-Magnet für hohen Schalldruck
- Verlängerte Polplatte für großen Hub
- Geeignet für Gehäuse ab 20 Liter
- Anwendung: Bandpass, Bassreflex oder Geschlossen



## SW-12

12 Inch Subwoofer  
Max. 400 Watt  
Part-No. : 350902



**AMP 4.600**

4 CH Amplifier

Max. 1000 Watt @ 2  $\Omega$

Part-No. : 350910



6 ANNIVERSARY

Frequency Response / Übertragungsbereich	15 Hz - 25.000 Hz
Input Sensitivity Level In / Eingangsempfindlichkeit Level In	250 mV ~ 4 V
High-pass / Subsonic / Hochpass / Subsonic	20 Hz ~ 240 Hz
Low-pass / Tiefpass	40 Hz ~ 400 Hz
Band-pass / Bandpass	20 Hz ~ 400 Hz
Q-Base / Bassanhebung	6, 12 dB @ 45 Hz
Input Impedance Stereo [ $\Omega$ ] / Anschlußimpedanz Stereo [ $\Omega$ ] - 2CH 4CH	2 x 2 stable AMP 2.500 4 x 2 stable AMP 4.600
Temperature Control Heatsink / Temperaturüberwachung Kühlkörper	70°C shut-down
Short Circuit Protection – Overload / Kurzschlußsicherung – Überlastung	Immediate shut-down
Softstart-Muting on / off / Softstart-Muting an / aus	1s delay
Dimensions: W x H x D / Abmessungen: B x H x T	320 x 52 x 302 mm AMP 2.500 370 x 52 x 302 mm AMP 4.600
Approval number / Zulassungsnummer	E11-10R



### AMP 2.500

2 CH Amplifier

Max. 800 Watt @ 2  $\Omega$

Part-No. : 350901

RAC GmbH & Co. KG

Kirchhausener Straße 44

74906 Bad Rappenau

Germany

Tel. +49 (0) 7066 / 9006-0

Fax +49 (0) 7066 / 9006-50

**[www.bull-audio.de](http://www.bull-audio.de)**

Vertrieb Deutschland

AIV GmbH & Co. KG

Spitzwegstr.18

74081 Heilbronn

Germany

Tel. +49 (0) 7131 / 5953-0

Fax +49 (0) 7131 / 5953-29

[info@aiv.de](mailto:info@aiv.de)

[www.aiv.de](http://www.aiv.de)

