



Technical Specifications:

| | | | |
|----------------------------------|---|---------|----------|
| Output power continous sinewave: | 105W/8Ω | 170W/4Ω | 0.1% THD |
| Output power pulsed: | 350W/2Ω | 410W/1Ω | 0.1% THD |
| Maximum continous current: | 6A | | |
| Maximum Pulsed current: | 20A (100ms burst) | | |
| Distortion THD: | 0.0087% 8Ω – 5Watt – 1Khz | | |
| Distortion TIM: | 0.011% 8Ω – 5Watt – 50Hz/7Khz 4:1 | | |
| Hum and Noise level: | -99.7dB ref: Max, output level | | |
| Bandwith: | DC – 160Khz -3dB 1W/8Ω | | |
| Gain: | 50x = 34dB 600mV for max output | | |
| Input impedance: | 47KΩ | | |
| Damping factor: | 600 | | |
| Slew rate: | 23V/uS | | |
| AC voltage: | 115VAC / 230VAC internal switch 50/60Hz +/-10% | | |
| Power consumption: | Idle 7VA – Max 550 VA | | |
| Powersupply: | 500VA torroid and 6x10.000uf | | |
| Protection: | Internal Fuse on powerrail only (no current limiting) | | |
| | Input mute on switch off | | |
| Inputs: | 2x RCA gold plated | | |
| Outputs: | 2x Binding post gold plated | | |
| Dimensions: | 440x88(95)x375mm WxH(with feet)xD | | |

april 2006