## 165 A3

## 3 way kit

- Painted DIN basket, 20% glass fiber filled ABS material Rigid basket, non-magnetic and
- non-resonant
- All weather woven glass fiber cone Dynamic bass and accurate midrange, humidity resistant
- Phase plug

Regulates the midrange outside the axis

- 25mm/2 layers voice coil on Kapton® support High power handling
- 72mm and 85mm magnet High efficiency
- Butyl surround Excellent cone damping
- 3-level adjustable tweeter Level adaptation according to location
- Low resistance self-induction coil Less loss, resistant to parasites



## Technical characteristics:

165mm [6.5"] Woofer

25mm (0.98") Voice coil

85mm (3.35") Magnet

100mm (3.94") Midrange

72mm (2.84") Magnet

TN44 inverted dome

3-way separate crossover 12/12dB/oct (300Hz-4kHz)

Adjustable tweeter level: +3, 0,-3dB

Max. power: 160W Nom. power: 80W

Sensitivity (2.8V/1m: 90dB

Frequency response: 55Hz - 20kHz

(Grilles supplied)

## It makes the difference:

- The new Access reference
- Excellent quality/price ratio
- 3-way kit sound quality



Voice coil permanent cooling • Aluminum inverted dome

Treble accuracy