

# 130 KR

## 2-way K2 Power kit

- K2 composite sandwich cone

### Impact and details

- Zamak chassis

### Strong, rigid and non-magnetic chassis

- Butyl surround

### Excellent reliability

- Engraved serial number

### Certificate of authenticity

- Adjustable tweeter 3 levels per stage of 3dB

### Installation flexibility

- Polypropylene capacitor

### Neutral reproduction of high frequencies

- Multi-wire air core inductor

### Resistant to parasites, maximum dynamic



- TNK inverted dome tweeter

### Smoothness and precision

- Neodymium ring magnet

### Very high linearity and dynamism

- Foam surround

### Extended frequency response

## Technical characteristics:

130mm (5") Woofer

25mm (1") Voice coil

85mm (3.5") Magnet

TNK inverted dome tweeter

Separate crossover : 12/12dB/oct (3.5kHz)

Adjustable tweeter level : {0,-3,-6dB}

Max. power : 140W

Nom. power : 70W

Sensitivity (2,83V/1m) : 90dB

Frequency response : 70Hz – 20kHz

Accessories : grilles supplied

## It makes the difference:

- Treble smoothness
- Dynamic and neutrality
- Precision of sound stage
- Tweeter sound level adjustment



**FOCAL**  
the Spirit of Sound